Axial fans **MPV A1EGSX**

The MPV A1EGSX is a portable gas freeing fan used for mechanical ventilation / gas freeing of cargo tanks on tankers. The fan is ATEX approved and satisfies the demands of the various classification societies.





Standard sizes 315 – 450 mm



Air flow 20 - 14.000

Summary

Design

The fan is lightweight and designed for maximum portability. Either to be equipped with water or air driven motor. The fan opening is designed to fit standard tank opening of ø318mm.

With capacities up to 14.000 m3/h. The PCD diameter can be adjusted to suit customer's requirements. The flexible duct has a loose flange connection to the fan, so it can be handled and stored separately.

Execution

The fan is made of sea water resistant aluminium, primed and painted. The wire guard is in stainless steel.

The fan can also be delivered in AISI 316 Execution

Impeller

Motor

EX proof antistatic reinforced polypropelene, dynamically balanced.

The fan is delivered with either water or air driven motor.

Customizations

- Special division circle / flange pattern
- Non-standard opening sizes

Accessories

General:

- Collapsible air duct (supply and exhaust)
- Flat air duct (only supply)
- Trolley

Water driven fans:

- Water hoses (inlet/outlet)
- Water hoses for high water pressure
- Different connections for water hose

Air driven fans

- Air hose for motor
- Air filter (recommended)
- Oiler (recommended for longer life) Silencer for air motor
- Manometer
- Regulator (with lock)

Gallery



Documentation

Downloads

Drawings

Detailed specifications

<u>\{ \}</u>